



# **AM090HB**



## **PRODUCT SPECIFICATIONS**

Internal Capacity 0.9 cu. ft.
Cooking Wattage 900 watts

Power Cord Approximately 3.33 ft. long

Control Type Electronic Touch Pads with Child Control Lock

Power Levels 10 Power Level Selections

LED Display Clock & Timer

Auto Cook Selections Baked Potato, Dinner Plate, Pizza
One-Touch Cook Pads Beverage, Popcorn, Frozen Vegetables

Auto Defrost Selections Weight & Time Defrost
Quick Defrost Defrost Based on Time
Kitchen Timer 99 minutes and 99 seconds

Door Opening Door Handle

Turntable 11 in. Diameter Glass Turntable

#### **INSTALLATION REQUIREMENTS**

Select a level surface that provide enough open space for the intake and/or outlet vents. A minimum clearance of 3.0 inches (7.5cm) is required between the oven and any adjacent walls. One side must be open. The minimum installation height is 3 feet.

Plug your oven into a standard household outlet. Be sure the voltage and the frequency is the same as the voltage and the frequency on the rating label. WARNING: Do not install oven over a range cooktop or other heat-producing appliance. If installed near or over a heat source, the oven could be damaged and the warranty would be void.

#### Countertop Installation

Remove all packing material and accessories. Examine the oven for any damage such as dents or broken door. Do not install if oven is damaged. Cabinet: Remove any protective film found on the microwave oven cabinet surface. Do not remove the light brown Mica cover that is attached to the oven cavity to protect the magnetron.

### **DIMENSIONS**

Width	18.62 in.
Depth	14.72 in.
Height	10.71 in.
Weight	24 lbs.
Carton Width	20.04 in.
Carton Depth	15.55 in.
Carton Height	11.65 in.
Shipping Weight	26 lbs.
Shipping Cube	2.1 cu. ft.

#### **ELECTRICAL**

A minimum 15 Amp electrical supply is required (20 Amp electrical supply preferred). A time delay fuse or circuit breaker and separate circuit is recommended.

120 V | 60 Hz | AC | 13 Amp grounded outlet



Absocold, P.O. Box 1545 Richmond, IN 47375 Toll-Free: 800-843-3714 Fax: 765-935-3450 www.absocold.com absocold@absocold.com



