



ARD101AB21R/L

Black
 Model: ARD101AB21R/L



FEATURES

- Environmentally Friendly – R600a Refrigerant and EPS-free Packaging
- Quiet Operation – 33 dB
- Durable and Easy to Clean Black Wrinkle Finish
- Adjustable Glass Shelf
- Fits Most Existing Absorption-Type Unit Cabinetry

PRODUCT SPECIFICATIONS

Energy	ENERGY STAR® Qualified - Tier I 241 KWH/Yr Energy Consumption 10% Less Energy Than Federal Standard
Defrost Type	Automatic Defrost
Refrigerant Type	R600a
Temperature Control	Full Range Control
Door Type	Easy-Clean Euro-Round Doors
Door Handles	Integrated Handles
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Compressor Noise Rating	33 dB
Cord Length	61 in.
Interior Shelves	1 Full-Width Adjustable Glass Shelf
Refrigerator Door Storage	Beverage Can Dispenser (6 cans) Tall Bottle Door Shelf
Leveling	2 Front Adjustable Leveling Feet
Capacity	1.0 cu. ft. Total Capacity

DIMENSIONS

Width	15.1 in.
Depth	16.1 in.
Height	19.3 in.
Weight	30.86 lbs.
Carton Width	17.1 in.
Carton Depth	18.5 in.
Carton Height	22 in.
Shipping Weight	35.27 lbs.
Shipping Cube	4.02 cu. ft.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended.

Electrical Requirements: 115 V | 60 Hz
 Running Amperage: 0.8 A

Absocold, P.O. Box 1545
 Richmond, IN 47375
 Toll-Free: 800-843-3714
 Fax: 765-935-3450
www.absocold.com
absocold@absocold.com

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be freestanding and must be installed at least 2" from the wall, at least 3/4" to 1" above the floor or carpet, 1" on sides, and 2" on top in order to let the air circulate freely around the unit.