



ARD161AB21R/L

 **Black**
Model: ARD161AB21R/L

 **Stainless**
Model: ARD161ABS21R/L



FEATURES

- Environmentally Friendly – R600a Refrigerant and EPS-free Packaging
- Quiet Operation – 33 dB
- Durable and Easy to Clean Black Wrinkle Finish
- Adjustable Glass Shelves
- Fits Most Existing Absorption-Type Unit Cabinetry

PRODUCT SPECIFICATIONS

Energy	ENERGY STAR® Qualified - Tier I 245 KWH/Yr Energy Consumption 10% Less Energy than Federal Standard
Defrost Type	Automatic Defrost
Refrigerant Type	R600a
Temperature Control	Full Range Control
Door Type	Easy-Clean Euro-Round Doors
Door Handles	Integrated Handles
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Compressor Noise Rating	33 dB
Cord Length	61 in.
Interior Shelves	2 Full-Width Adjustable Glass Shelves
Refrigerator Door Storage	Beverage Can Dispenser (6 cans) Tall Bottle Door Shelf
Leveling	2 Front Adjustable Leveling Feet
Capacity	1.6 cu. ft. Total Capacity

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be freestanding and must be installed at least 2" from the wall, at least 3/4" to 1" above the floor or carpet, 1" on sides, and 2" on top in order to let the air circulate freely around the unit.

DIMENSIONS

Width	17.7 in.
Depth	17.7 in.
Height	19.8 in.
Weight	32.4 lbs.
Carton Width	19.5 in.
Carton Depth	20.1 in.
Carton Height	22.6 in.
Shipping Weight	37.47 lbs.
Shipping Cube	5.13 cu. ft.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended.

Electrical Requirements: 115 V | 60 Hz
Running Amperage: 0.8 A

Absocold, P.O. Box 1545
Richmond, IN 47375
Toll-Free: 800-843-3714
Fax: 765-935-3450
www.absocold.com
absocold@absocold.com