***ABSOCOLD**

Absocold[®] 1.6 Cu. Ft. Single Door Hospitality Refrigerator ENERGY STAR[®] Qualified | Auto-Defrost





FEATURES

- Environmentally Friendly R600a Refrigerant and EPS-free Packaging
- Quiet Operation 33 dB
- Durable and Easy to Clean Black Wrinkle Finish
- Adjustable Glass Shelves
- Fits Most Existing Absorption-Type Unit Cabinetry

PRODUCT SPECIFICATIONS

Energy

Defrost Type Refrigerant Type Temperature Control Door Type Door Handles Door-Swing Compressor Noise Rating Cord Length Interior Shelves Refrigerator Door Storage Leveling

Leveling Capacity **ENERGY STAR® Qualified - Tier I** 245 KWH/Yr Energy Consumption 10% Less Energy than Federal Standard Automatic Defrost R600a **Full Range Control** Easy-Clean Euro-Round Doors **Integrated Handles** Reversible (Factory Standard, Right-Hand Hinge) 33 dB 61 in. 2 Full-Width Adjustable Glass Shelves Beverage Can Dispenser (6 cans) Tall Bottle Door Shelf 2 Front Adjustable Leveling Feet 1.6 cu. ft. Total Capacity

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be freestanding and must be installed at least 2" from the wall, at least 3/4" to 1" above the floor or carpet, 1" on sides, and 2" on top in order to let the air circulate freely around the unit.

ARD161ABS21R/L



Stainless Model: ARD161ABS21R/L



| 17.7 in. |
|--------------|
| 17.7 in. |
| 19.8 in. |
| 32.4 lbs. |
| 19.5 in. |
| 20.1 in. |
| 22.6 in. |
| 37.47 lbs. |
| 5.13 cu. ft. |
| |

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended.

Electrical Requirements: 115 V | 60 Hz Running Amperage: 0.8 A

> Absocold, P.O. Box 1545 Richmond, IN 47375 Toll-Free: 800-843-3714 Fax: 765-935-3450 www.absocold.com absocold@absocold.com