



ARD204AB21R/L

Black
Model: ARD204AB21R/L

Stainless Door
Model: ARD204ABS21R/L



FEATURES

- Quiet Operation
- Special Quick Chill 'N Snooze® Functions
- 2 Full-Width Removable Shelves
- Fits Most Existing Absorption-Type Unit Cabinetry
- Door Beverage Can Dispenser

PRODUCT SPECIFICATIONS

Energy	ENERGY STAR® Qualified - Tier I 249 KWH/Yr Energy Consumption 10% Less Energy than Federal Standard
Quick Chill 'N Snooze®	Snooze® Function (8 hours) Quick Chill® Function (2 hours)
Defrost Type	Automatic Defrost
Refrigerant Type	R600a
Door Type	Easy-Clean Euro-Round Doors
Door Handles	Integrated Handles
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Cord Length	77 in.
Interior Shelves	2 Full-Width Removable Shelves
Refrigerator Door Storage	Beverage Can Dispenser (5 cans) 2 Door Shelves
Leveling	2 Front Adjustable Leveling Feet
Capacity	2.0 cu. ft. Total Capacity

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be freestanding and must be installed at least 2" from the wall, 3/4" to 1" above the floor or carpet, 1" on sides, and 2" on top in order to let the air circulate freely around the unit.

Suite Fridge® hospitality refrigerators are specifically designed for commercial hotel applications only and are not intended for medical or consumer residential applications.

DIMENSIONS

Width	18.5 in.
Depth	19 in.
Height	22.375 in.
Weight	40 lbs.
Carton Width	21 in.
Carton Depth	20 in.
Carton Height	23.5 in.
Shipping Weight	44 lbs.
Shipping Cube	5.7 cu. ft.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended.

Electrical Requirements: 115 V | 60 Hz
Running Amperage: 0.9 A

Absocold, P.O. Box 1545
Richmond, IN 47375
Toll-Free: 800-843-3714
Fax: 765-935-3450
www.absocold.com
absocold@absocold.com

Patent, Copyright and Trademark Information
This product is covered by US Patent #7,634,918.
Other US Patents Pending.