



ARD244AB21R/L

 **Black**
 Model: ARD244AB21R/L

 **White**
 Model: ARD244AW21R/L



FEATURES

- Quiet Operation
- Lower Shelf Accepts 2-Liter Bottles
- Full-Width Adjustable Wire Shelves
- Fits Most Existing Absorption-Type Unit Cabinetry

PRODUCT SPECIFICATIONS

Energy	ENERGY STAR® Qualified - Tier III 223 KWH/Yr Energy Consumption 20% Less Energy than Federal Standard
Defrost Type	Automatic Defrost
Refrigerant Type	R600a
Temperature Control	Full Range Control
Door Type	Easy-Clean Euro-Round Doors
Door Handles	Integrated Handles
Door-Swing	Reversible (Factory Standard, Right-Hand Hinge)
Interior Shelves	2 Full-Width Adjustable Wire Shelves
Refrigerator Door Storage	2 Full-Width Shelves Lower Shelf accepts 2-Liter Bottles
Leveling	2 Front Adjustable Leveling Feet
Capacity	2.8 cu. ft. Total Capacity

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be freestanding and must be installed at least 2" from the wall, and the cabinet bottom is at least 3/4" to 1" above the loor or carpet, 1" on sides, 2" on top in order to let the air circulate freely around the unit.

DIMENSIONS

Width	18.5 in.
Depth	20.0 in.
Height	25.0 in.
Weight	39.0 lbs.
Carton Width	20.25 in.
Carton Depth	23.75 in.
Carton Height	25.625 in.
Shipping Weight	44.0 lbs.
Shipping Cube	7.2 cu. ft.

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended.

Electrical Requirements: 115 V | 60 Hz
 Running Amperage: 0.8 A

Absocold, P.O. Box 1545
 Richmond, IN 47375
 Toll-Free: 800-843-3714
 Fax: 765-935-3450
www.absocold.com
absocold@absocold.com