



ARD244AW21R/L

 **Black**
Model: ARD244AB21R/L

 **White**
Model: ARD244AW21R/L



FEATURES

- Quiet Operation
- Lower Shelf Accepts 2-Liter Bottles
- Full-Width Adjustable Wire Shelves
- Fits Most Existing Absorption-Type Unit Cabinetry

PRODUCT SPECIFICATIONS

| | |
|---------------------------|---|
| Energy | ENERGY STAR® Qualified - Tier III 223 KWH/Yr Energy Consumption 20% Less Energy than Federal Standard |
| Defrost Type | Automatic Defrost |
| Refrigerant Type | R600a |
| Temperature Control | Full Range Control |
| Door Type | Easy-Clean Euro-Round Doors |
| Door Handles | Integrated Handles |
| Door-Swing | Reversible (Factory Standard, Right-Hand Hinge) |
| Interior Shelves | 2 Full-Width Adjustable Wire Shelves |
| Refrigerator Door Storage | 2 Full-Width Shelves Lower Shelf accepts 2-Liter Bottles |
| Leveling | 2 Front Adjustable Leveling Feet |
| Capacity | 2.8 cu. ft. Total Capacity |

INSTALLATION REQUIREMENTS

Remove all packing material and tape. Install on a level floor or well-supported counter. Avoid any direct sunlight, heat source, or moisture. This product is designed to be freestanding and must be installed at least 2" from the wall, and the cabinet bottom is at least 3/4" to 1" above the floor or carpet, 1" on sides, 2" on top in order to let the air circulate freely around the unit.

DIMENSIONS

| | |
|-----------------|-------------|
| Width | 18.5 in. |
| Depth | 20.0 in. |
| Height | 25.0 in. |
| Weight | 39.0 lbs. |
| Carton Width | 20.25 in. |
| Carton Depth | 23.75 in. |
| Carton Height | 25.625 in. |
| Shipping Weight | 44.0 lbs. |
| Shipping Cube | 7.2 cu. ft. |

ELECTRICAL

A minimum 15 AMP electrical supply is required (20 AMP electrical supply preferred). A time-delay fuse or circuit breaker and separate circuit is recommended.

Electrical Requirements: 115 V | 60 Hz
Running Amperage: 0.8 A

Absocold, P.O. Box 1545
Richmond, IN 47375
Toll-Free: 800-843-3714
Fax: 765-935-3450
www.absocold.com
absocold@absocold.com